

**SLITTER-REWINDER**  
**EASYline US-550QC(Big Diameter)**

**for converting and checking  
of narrow web materials:**



**1) Steel plate construction**

- Welded steel frame
- Covered with painted steel plates
- Front and bottom plate made of steel
- Sides and covers made of sheet steel
- Electronics integrated in the machine housing
- Supply 400 volts

**2) Unwinder with pneumatic air shaft**

- Magnetic powder brake
- Right / left unwinding possible
- Tension controller
- Pneumatic air shaft 76 mm
- Roll diameter max.  $\varnothing$  1.200 mm
- Coil weight max. 400 kg
- Material width 60 mm to 550 mm

**3) Splice table**

- Splice table from sheet steel
- Four magnetic clamping jaws
- Knife guide for cross or diagonal cut

**4) Web guiding system**

- By two photoelectric sensor

**5) Counter**

- Changeable from label counter to meter counter

**6) Drive unit**

- Steel roller
- Rubberized pressure roller
- Adjustable pressure of the pressure roller
- Driven by electric motors
- Web speed up to 100m/min, depending on the product

### 7) suction

- Axial fan for suction of waste strip

### 8) slitter

- Scissor cutting system with rotary blades
- Six pieces of upper blade
- Six pieces anvil blade rings
- Minimum cutting width 18mm / 10mm as option



### 9) 2 piece rewinding shafts

- Pneumatic air shaft for 1,5 inch cores  
Other diameter on require
- Tension adjustable by magnetic powder clutch
- Roll diameter max. 350 mm
- Max. axle weight 120 kg

### 10) Operating and control unit

- Main switch
- Control "ON" button
- START / STOP button
- Emergency Stop button
- Variable speed by potentiometer
- Meter and label counter switchable
- Lettering in English or local language
- Automatic machine Stop when reaching the pre-selected number of meters / labels
- Electronic components integrated in the machine housing

- Web direction from right to left
- Manual and Documentation in English or local language
- CE Declaration of Conformity

### 11)Material to be processed

- Adhesive labels, paper, foil, laminates up to 600 grs/m<sup>2</sup>

**Total price of the machine** **see offer**

#### Technical data:

Voltage:	400 Volt
Electrical power:	5,5 KW
Current:	16 Amps
Frequency:	50 Hz
Pneumatic air supply:	6 bars
Length x width x height:	2.100 mm x 1.200 mm x 1.400 mm
Weight:	about 1.600 kg

#### Optionen:

- Airshaft from 1 up to 6 Inch
- Frictionshafts
- Pneumatic knife holder
- Razor blade holder
- Back slit Unit
- Label counter for clear of clear Material
- Finishing for slit tapes and materials with open gluing

